



**TASKI®**

**Jontec Technique**



**F2h**

## Semi-permanent sealer

### Description

TASKI® Jontec Technique is a semi permanent floor sealer for the basic treatment of most types of porous hard floors. Specific polymers used in the product fill the pores, facilitate adhesion and help reduce the consumption of further coats of floor emulsion.

By ensuring the proper adhesion, subsequent floor emulsions will show greater durability.

### Features

- Semi-permanent sealer ideal for use as a base coat.
- Can be used on all internal resilient floors such as vinyl and porous composite tiles as well as vinyl asbestos tiles
- Seals and protects against stains.
- Technique enhances the appearance of old and worn out floors when used with a Diversey finish.
- Provides protection to floor against a wide variety of damaging and staining substances.

### Benefits

- Highly resistant to common floor spills.
- Provides greater protection of floors.

### Application areas

- Retail
- Education
- Government
- Healthcare
- Institutional Facilities





**TASKI®**

**Jontec Technique**



**F2h**

## Semi-permanent sealer

### Directions for use

#### Application

1. Strip old coatings using a Diversey stripper according to label directions. Treat only fully stripped, thoroughly rinsed and completely dry floors.
2. Pour the product sparingly onto floor and evenly spread with a polish applicator in lanes of 1-1.5m with the lanes overlapping while still wet.
3. Allow the floor to dry completely (typically 20-40 minutes). Apply a second coat on very porous floors.
4. Allow to dry completely before applying 2-4 coats of Diversey finish.

#### Removal

1. Use Diversey stripper diluted according to label directions. Allow at least 10 minutes contact time. Do not allow stripper to dry. Rewet with additional stripper solution if required.
2. Scrub thoroughly with a brush or aggressive pad. If coats are heavy, a second strip may be required.
3. Rinse thoroughly and dry completely.

#### Top Coat Removal – Unbuffered Floors

1. Remove top coat finish with blue pad and Diversey alkaline heavy duty cleaner according to label directions.
2. Rinse and allow floor to dry.

Technical data			
Appearance	Milky white liquid	Odour	Product specific
pH	8.5 (neat)	Specific Gravity	1.03
Coverage	30 – 40m <sup>2</sup> per litre	Drying time	20-40 mins
Dilution	Neat		

*The above data is typical of normal production and should not be taken as a specification.*

Product	Pack size	SKU Code	Availability
TASKI® Jontec Technique	2 x 5L	7513198	AU & NZ

### Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet. Store in original container. Avoid extremes of temperature and humidity.

### Product compatibility

Under recommended conditions of use, TASKI® Jontec Technique is suitable on all internal resilient floors such as vinyl and porous composite tiles. Do not use on linoleum and rubber floors.

### Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available online at [www.diversey.com](http://www.diversey.com) or by calling Toll free: Australia, 1800 647 779 or New Zealand, 0800 803 615.

For additional information, please contact us at:  
Diversey Australia Pty Ltd Toll free: 1800 647 779, Diversey New Zealand Ltd Toll free: 0800 803 615 [www.diversey.com](http://www.diversey.com).