

Pinnacle

Ultra High Speed Floor Finish

Pinnacle is Australia's #1 floor finish. Pinnacle is a heavy duty premium performance UHS floor finish that provides exceptional "wet look" gloss, low marking and ease of maintenance. Pinnacle is easy to apply and maintain with choice of a restorer system if needed.

Precautions:

- ▶ Do not dilute.
- ▶ Do not use on surfaces colder than 7°C/45°F.
- ▶ To avoid contamination, do not return unused finish to original container.
- ▶ Not intended for outdoor use.

Excellent Performance

- ▶ Provides a superior "wet look" gloss with diamond like brilliance and clarity
- ▶ Great burnish response that "pops" with propane, battery or electric equipment
- ▶ Durable, heavy duty formulation
- ▶ Superior resistance to dirt embedment, scratching, scuffing and marking

Easy-to-Use

- ▶ Easy to apply using standard mop or applicator
- ▶ Enables flexibility in maintenance procedures and burnishing frequency while still maintaining a great appearance
- ▶ Can be used on most types of floors and is easy to maintain

Designed For

- ▶ Retail
- ▶ Education
- ▶ Government
- ▶ Healthcare
- ▶ Institutional Facilities



Directions for Use

Application

1. Blockade areas to be stripped or finished. Strip old coatings using a Diversey Care stripper according to label directions. Allow floor to dry.
2. Apply one coat of Pinnacle using a clean finish mop.
3. Allow coat to dry for 30-45 minutes depending on drying conditions. Temperature, humidity and ventilation may affect drying time.
4. Repeat steps 2 & 3 to apply 3-6 further coats for the desired gloss. Allow 30-45 minutes drying time between coats. Allow finish to cure for 24 hours before burnishing.

Maintenance

1. Dust mop or sweep to remove dust or dirt.
2. Clean the floor with a mop or an automatic scrubber using the recommended Diversey Care brand cleaner according to label directions.
3. Maintain gloss by periodic recoating and UHS burnishing using an approved pad . Speed 1500-3000 rpm.
4. Pinnacle can also be maintained periodically with a Diversey Care brand maintainer according to label directions. Burnish using appropriate pads.

Recoating

1. Dust mop or sweep to remove dust or dirt.
2. Deep scrub the floor with a mop or an automatic scrubber.
3. When dry, blockade area and apply 2-3 uniform coats of Pinnacle using a clean finish mop.
4. Allow 30-45 minutes drying time between coats. Temperature, humidity and ventilation may affect drying time. Allow finish to cure for 24 hours before burnishing.

Technical Data

Description	
Appearance	Opaque white liquid
Odour	Characteristic odour
pH (concentrate)	9.0
Specific Gravity	1.03
Coverage	50 – 60 m ² per liter
Slip classification	Class F (AS/NZS 4586:2004)
Maintenance speed	1500 – 3000+ rpm

Available Items

Code	Description	Pack Size	Dilution	Availability
5519645	Pinnacle	2x5L	Neat	ANZ

These figures are typical values and should not be interpreted as specifications.

Safe handling and storage information:

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet. Store in original container. Avoid extremes of temperature and humidity. Do not dilute. To avoid contamination, do not return unused finish to original container.

Product compatibility:

Under recommended conditions of use, Pinnacle is suitable for use on most floor types. Non-resilient (porous) floors must be sealed first before applying finish. Ideal for low maintenance, ultra high speed program. Do not use on surfaces colder than 7°C /45°F. Not intended for outdoor use.

Safety Reminder:

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available online at www.sealedair.com or by calling Toll free: Australia, 1800 647 779 or New Zealand, 0800 803 615.

For additional information, please contact us at:

Diversey Australia Pty Ltd Toll free: 1800 647 779, Sealed Air (New Zealand) Toll free: 0800 803 615
www.sealedair.com

© 2016 Sealed Air Corporation. All Rights Reserved.