

Vectra

Sealer/Finish



Vectra is a high performance fast curing floor finish for use on all internal resilient floors such as vinyl and porous composite tiles. Vectra delivers diamond like brilliance and clarity across a wide variety of surfaces. Vectra can be top coated over any Diversey sealer for even more flexible floorcare solutions.

Features:

- ▶ Can be used as a scrub and recoat finish
- ▶ Resists scuffing, dirt and marking
- ▶ Vectra gives high levels of gloss, durability and levelling with good colour stability.
- ▶ Suitable for most types of floors
- ▶ Easy to maintain
- ▶ Diamond like brilliance and clarity

Benefits:

- ▶ Vectra is fast curing and extremely hard, with excellent adhesion and scuff resistance which reduces the need for recoats, saving time and labour
- ▶ Resists black heel marks and scuffs
- ▶ Responds well to spray buffing which means floor will retain its gloss for longer between recoats
- ▶ Excellent gloss and clarity ensuring long term floor appearance

Designed For

- ▶ Retail
 - ▶ Education
 - ▶ Government
 - ▶ Healthcare
 - ▶ Institutional Facilities
-

Use Overview

Directions for Use

Application

1. Strip old coatings using a Diversey stripper according to label directions. Allow floor to dry.
2. Apply one coat of Vectra using a clean mop or applicator.
3. Allow coats to dry for 20-30 minutes depending on drying conditions.
4. Apply 3-4 further coats of Vectra using a clean mop required.

Maintenance

1. Dust, mop or sweep to remove and dust or dirt.
2. Clean floor with a Diversey cleaner diluted in cold water according to label directions.
3. Maintain the gloss of Vectra using periodic recoating or spray buffing using an approved pad.
4. Wash out all equipment before storage.

Before recoating

1. Dust mop or sweep to remove and dust or dirt.
2. Deep scrub floor using an approved pad and Diversey cleaner diluted in cold water according to label directions.
3. When dry, apply 2-3 coats of Vectra using a clean mop as required.
4. Allow coats to dry for 20-30 minutes depending on drying conditions.

Technical data

| Description | |
|--------------------------------|---------------------------------|
| Appearance | Opaque white liquid |
| Odour | Ammonia odour |
| pH (concentrate) | 8.3 - 8.8 |
| Shelf life | 2 years |
| Specific Gravity @ 20°C | 1.03 |
| Coverage | 50 – 60m ² per litre |
| Slip classification | Class F (AS/NZS 4586:2004) |
| Maintenance speed | 900 - 1500 rpm |

Available Items

| Code | Description | Pack Size | Dilution | Availability |
|---------|-------------|-----------|----------|--------------|
| 5687631 | Vectra | 2 x 5L | Neat | AU & NZ |

These figures are typical values and should not be interpreted as specifications.

Safe handling and storage information:

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet. Store in original container. Avoid extremes of temperature and humidity.

Product compatibility:

Under recommended conditions of use, Vectra is suitable for use on most floor types. Non-resilient (porous) floors must be sealed first before applying finish. Ideal for low maintenance, spray buffing program.

Safety Reminder:

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available online at www.diversey.com or by calling Toll free: Australia, 1800 647 779 or New Zealand, 0800 803 615.

For additional information, please contact us at:
Diversey Australia Pty Ltd Toll free: 1800 647 779, Diversey New Zealand Ltd Toll free: 0800 803 615
www.diversey.com